


Drivers DC



Drivers

n°	Power Input/Volt	Current Output	Voltage Output DC	LED	W	⌚ (u/h)			⤵ (%)	A (mm)	B (mm)	C (mm)	Colour	IP	
1 FL 912001	230	250 < 1000	-	LED	20	50000	-	-	1-10V	111	52	24	-	GREY	20
Stabilized Adjustable current source one channel 250-1000mA OR 250-500mA Two Channel • Use only single channel • More drivers on 1 dimmer, only 1-10V.															
2 MM 06680	230	350 mA	30-40V	LED	14	50000	-	-	YES*	116	55	25	-	WHITE	20
3 MM 02509	230	460 mA	20-23V	LED	10	50000	-	-	1-10V	147	50	32	-	WHITE	20
4 MM 02962	230	500 mA	17-23V	LED	10	50000	-	-	1-10V	147	50	32	-	WHITE	20
5 MM 05465	230	600 mA	15-30V	LED	42	50000	-	-	1-10V	95	30	32	-	BLACK	20
6 MM 05466	230	800 mA	19-37V	LED	52	50000	-	-	1-10V	176	53	35	-	SILVER	67
7 MM 08194	230	900mA	30-57V	LED	48	50000	-	-	NO	145	48	32	-	WHITE	20
7 MM 06105	230	1400 mA	21.5-36V	LED	48	50000	-	-	NO	155	50	34	-	WHITE	20
7 MM 06241	230	1400 mA	17.5-29V	LED	38	50000	-	-	NO	155	50	34	-	WHITE	20
8 MM 05570	230	1050mA	25-28V	LED	36	50000	-	-	NO	120	78	35	-	WHITE	20

*PHASE CUT
Omgevingstemp. /Temp. ambiente - 30 °C > + 40 °C

1 FL912001 Connection Scheme

for 250-500mA

for 500-1000mA

