



ENSIO Floodlight (Integrated) - IP66



Product Code:

FFL70000v0

Electrical Data	
Voltage (V)	220-240V
Power Factor	>0.9
Product Data	
Product Wattage (W)	90
Beam Angle (°)	110 [Symmetric], 70 [Asymmetric]
Tilting Angle (°)	90
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K), Daylight (6500K)
Colour Render Index (Ra)	Ra80
Colour	Black (BK24)
Materials	Aluminum housing with anodizing aluminum louvre and PC cover
Protection Class	Class I
Dimmable	No
Operating Temperature	-30 ° C to +50 ° C
Weight (g)	4324
Application	Billboards, Gate areas, Pillar Facades, Signages
Performance Data	
Max. Luminous Intensity (cd)	5500 [Symmetric], 6800 [Asymmetric]
Luminous Flux (lm)	10500 [3000K], 11000 [4000K, 6500K]
Luminous Efficacy (lm/W)	117 [3000K], 122 [4000K, 6500K]
Rated Life (hrs)	50000
IP Rating	IP66
Product Dimensions	
Length (mm)	335
Width (mm)	296
Height (mm)	72

Product Code: FFL70000v0

MEGAMAN® 2005-2017. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc