


MALO Batten (Integrated)




White




IP20

Class II



Integrated LED Luminaire
FIB70000v1



Product Code:

FIB70000v1

Electrical Data

Voltage (V)	220-240V
-------------	----------

Product Data

Product Wattage (W)	15
Beam Angle (°)	110
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K), Daylight (6500K)
Colour Render Index (Ra)	>Ra80
Colour	White (WH12)
Materials	Polycarbonate
Protection Class	Class II
Dimmable	No
Operating Temperature	-30 ° C to +40 ° C
Weight (g)	355
Application	Cabinets, Corridors and Staircases, Factories, Residential, Warehouses

Performance Data

Luminous Flux (lm)	1500
Luminous Efficacy (lm/W)	100
Rated Life (hrs)	50000
IP Rating	IP20

Product Dimensions


Length (mm)	600
Width (mm)	75
Height (mm)	39

Product Code: FIB70000v1

MEGAMAN® 2005-2017. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc



m	Lux	Ø cm
0.5	1600	143
1	400	286
1.5	178	428
2	100	571

Beam angle = 110°