



LED PAR30S


Model No.: LR3010.5-WFL
Voltage (V): 220-240
Rated Wattage (W): 10.5



lightplus
 A bright vision on light

Lamp Base	Rated Lamp Life (hrs)	Diameter (mm)	Length (mm)	Total Luminous Flux (lm)	Rated Luminous Flux in 90° cone (lm)	Rated Beam Angle (°)	Max. Luminous Intensity (cd)	Colour Rendering Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 100% of the Full Light Output(sec)	Switching Cycles (times)	Colour Consistency (SDCM)	Lumen Maintenance at the End of Lamp Life (%)	Energy Label (EEL)
				lm	Φ_{use}		cd	CRI	PF				SDCM	(%)	
Warm White (2800K)															
E27	15,000	95	88	700	635	35	850	80	>0.5	<0.5	Instant full light	>1,000,000	<6	≥70	A
Cool White (4000K)															
E27	15,000	95	88	700	635	35	850	80	>0.5	<0.5	Instant full light	>1,000,000	<6	≥70	A

Operating Temperature (°C) : -30 to +40
Mercury Content (mg): N/A



LED PAR30S



Conventional PAR30S

Spectral power distribution

